EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S1	0	(713/200.ccls.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/26 17:30
S2	3588	reset AND key AND ("713".clas. OR "726".clas. OR "380".clas.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/05/15 16:17
S3	426	administrator AND (flag OR parameter) AND (reset OR replacement) AND key AND ("713".clas. OR "726".clas. OR "380".clas.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/05/15 16:30
S4	471	(determine OR determining OR determined OR check OR checking OR checked) AND (default OR original) AND administrator AND (flag OR parameter) AND (reset OR resetting OR replacement OR replaced OR replacing) AND key AND ("713".clas. OR "726".clas. OR "380".clas.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/05/15 16:32
S5	211	secure AND account AND (determine OR determining OR determined OR check OR checking OR checked) AND (default OR original) AND administrator AND (flag OR parameter) AND (reset OR resetting OR replacement OR replaced OR replacing) AND key AND ("713".clas. OR "726".clas. OR "380".clas.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/05/15 16:40
S6	8	key recovery AND secure AND account AND (determine OR determining OR determined OR check OR checking OR checked) AND (default OR original) AND administrator AND (flag OR parameter) AND (reset OR resetting OR replacement OR replaced OR replacing) AND key AND ("713".clas. OR "726".clas. OR "380".clas.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/05/16 07:36

EAST Search History

S7	11	flag AND (key reset OR key replacement OR key re$1authentication OR key re$1validation) AND recovery AND key AND ("713".clas. OR "726".clas. OR "380".clas.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/05/16 07:44
S8	842	(recovery OR replacement) AND flag AND (key OR certificate OR signature) AND ("713".clas. OR "726".clas. OR "380".clas.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/05/16 07:45
S9	2	secure value AND (database OR data storage OR data center) AND (recovery OR replacement) AND flag AND (key OR certificate OR signature) AND ("713".clas. OR "726".clas. OR "380".clas.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/05/16 08:04
S10	1322	(determine OR determined OR determining) AND (database OR data storage OR data center) AND (recovery OR recovered OR recovering OR replacement OR replaced OR replacing OR generation OR generate OR generated OR generating) AND flag AND (key OR certificate OR signature) AND ("713".clas. OR "726".clas. OR "380".clas.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/05/16 08:05
S11	1240	process AND (determine OR determined OR determining) AND (database OR data storage OR data center) AND (recovery OR recovered OR recovering OR replacement OR replaced OR replacing OR generation OR generate OR generated OR generating) AND flag AND (key OR certificate OR signature) AND ("713".clas. OR "726".clas. OR "380".clas.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/05/16 08:06
S12	321	default AND reset AND process AND (determine OR determined OR determining) AND (database OR data storage OR data center) AND (recovery OR recovered OR recovering OR replacement OR replaced OR replacing OR generation OR generate OR generated OR generating) AND flag AND (key OR certificate OR signature) AND ("713".clas. OR "726".clas. OR "380".clas.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/05/16 08:07

S13	109	(administrator OR admin) AND default AND reset AND process AND (determine OR determined OR determining) AND (database OR data storage OR data center) AND (recovery OR recovered OR recovering OR replacement OR replaced OR replacing OR generation OR generate OR generated OR generating) AND flag AND (key OR certificate OR signature) AND ("713".clas. OR "726".clas. OR "380".clas.) AND (@pd<"20040409" or @ad<"20040409" or @prad<"20040409" or @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/05/16 08:07
S14	918	reset AND flag AND key AND privilege AND process AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/26 17:31
S15	0	reset AND flag AND key AND privilege AND process AND 713/200.ccls. AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/26 17:31
S16	136	reset AND flag AND key AND privilege AND process AND "713".clas. AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/26 17:33
S17	133	user AND reset AND flag AND key AND privilege AND process AND "713".clas. AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/26 17:33
S18	130	level AND user AND reset AND flag AND key AND privilege AND process AND "713".clas. AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/26 17:34
S19	49	intervention AND level AND user AND reset AND flag AND key AND privilege AND process AND "713".clas. AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 07:53
S20	751	access AND level AND user AND reset AND flag AND key AND process AND ("713".clas. OR "726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 07:55
S21	200	access AND level AND user AND reset AND flag AND key AND process AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 07:56

S22	102	access control AND level AND user AND reset AND flag AND key AND process AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 07:56
S23	87	operating system AND access control AND level AND user AND reset AND flag AND key AND process AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:05
S24	0	operating system AND access control AND level AND user AND reset AND flag AND key reset AND process AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:05
S25	0	operating system AND access control AND level AND user AND reset AND flag AND key recovery AND process AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:05
S26	33	recovery AND operating system AND access control AND level AND user AND reset AND flag AND key AND process AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:42
S27	6	administrator reset AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:45
S28	0	root AND account reset AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:45
S29	0	root reset AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:45
S30	0	administrative key reset AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:45

S31	8	key reset AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:46
S32	18	password reset AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:47
S33	0	backdoor AND password reset AND ("726". clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:47
S34	0	back door AND password reset AND ("726". clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:47
S35	13	(administrator OR administrative OR root) AND password reset AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 08:59
S36	7	password recovery AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 09:00
S37	199	reset AND default AND password AND ("726".clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 09:00
S38	9	reset AND default password AND ("726". clas.) AND (@pd<"20040206" or @ad<"20040206" or @prad<"20040206" or @rlad<"20040206")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 09:00
S39	2	"5991882".pn.	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 09:25
S40	2	"5241598".pn.	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2007/11/27 10:45

EAST Search History

S41	2	"5375243".pn.	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 14:22
S42	2	"5115508".pn.	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 14:23
S43	8	"20030182584".pn. | "6370649".pn. | "6725382".pn. | "5719941".pn.	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 14:23
S44	4796	(713/1,182.ccls. | 380/277,286,59.ccls. | 726/1,2,6.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:04
S45	5127	(713/1,182.ccls. | 380/277,286,59.ccls. | 726/1,2,6,16-18.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:05
S46	270	flag AND (password OR key) AND reset$4 AND (713/1,182.ccls. | 380/277,286,59. ccls. | 726/1,2,6,16-18.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:05
S47	121	flag AND password AND reset$4 AND (713/1,182.ccls. | 380/277,286,59.ccls. | 726/1,2,6,16-18.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:05
S48	10	flag AND (password NEAR reset$4) AND (713/1,182.ccls. | 380/277,286,59.ccls. | 726/1,2,6,16-18.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:41
S49	16	flag AND ((password | key) NEAR reset$4) AND (713/1,182.ccls. | 380/277,286,59. ccls. | 726/1,2,6,16-18.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:41

S50	793	flag AND ((password | key) NEAR reset$4) AND (@pd< "20040409" | @ad< "20040409" | @prad< "20040409" | @rlad< "20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:44
S51	9	herman.in. AND (713/1,182.ccls. | 380/277,286,59.ccls. | 726/1,2,6.ccls.) AND (@pd< "20040409" | @ad< "20040409" | @prad< "20040409" | @rlad< "20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:45
S52	11	herman.in. AND (713/1,182.ccls. | 380/277,286,59.ccls. | 726/1,2,6,16-18. ccls.) AND (@pd< "20040409" | @ad< "20040409" | @prad< "20040409" | @rlad< "20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:45
S53	17	herman.in. AND (713/1,182.ccls. | 380/277,286,59.ccls. | "726".clas.) AND (@pd< "20040409" | @ad< "20040409" | @prad< "20040409" | @rlad< "20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:48
S54	27	herman.in. AND ("713".clas. | 380/277, 286,59.ccls. | "726".clas.) AND (@pd< "20040409" | @ad< "20040409" | @prad< "20040409" | @rlad< "20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:50
S55	45	herman.in. AND ("713".clas. | "380".clas. | "726".clas.) AND (@pd< "20040409" | @ad< "20040409" | @prad< "20040409" | @rlad< "20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:52
S56	45	herman.in. AND ("713".clas. | "380".clas. | "726".clas.)	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:54
S57	565	(user | client) AND flag AND ((password | key) NEAR reset$4) AND (@pd< "20040409" | @ad< "20040409" | @prad< "20040409" | @rlad< "20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:56
S58	398	(access | privilege) AND (user | client) AND flag AND ((password | key) NEAR reset$4) AND (@pd< "20040409" | @ad< "20040409" | @prad< "20040409" | @rlad< "20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:56
S59	360	value AND (access | privilege) AND (user | client) AND flag AND ((password | key) NEAR reset$4) AND (@pd< "20040409" | @ad< "20040409" | @prad< "20040409" | @rlad< "20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:58

S60	0	value AND (access | privilege) AND (user | client) AND flag AND ((password | key) NEAR reset$4) AND ("713".clas. | "726". clas. | "380".clas.) (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:59
S61	0	value AND flag AND ((password | key) NEAR reset$4) AND ("713".clas. | "726". clas. | "380".clas.) (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:59
S62	51	value AND flag AND ((password | key) NEAR reset$4) AND ("713".clas. | "726". clas. | "380".clas.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:59
S63	41	value AND (access | privilege) AND (user | client) AND flag AND ((password | key) NEAR reset$4) AND ("713".clas. | "726". clas. | "380".clas.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 15:59
S64	59	flag AND ((password | key) NEAR reset$4) AND ("713".clas. | "726".clas. | "380".clas.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 16:12
S65	8	flag AND ((password | key) NEAR reset$4) AND ("713".clas. | "726".clas. | "380".clas.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409") AND (NOT S62)	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 16:13
S66	3	flag AND resetting password$1 AND ("713".clas. | "726".clas. | "380".clas.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409") AND (NOT S62)	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 16:24
S67	29	flag AND setting password$1 AND ("713". clas. | "726".clas. | "380".clas.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409") AND (NOT S62)	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/05/27 16:24
S69	6	"5241598".pn. | "5115508".pn. | "20030182584".pn.	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/06/02 08:45

S70	55	value AND flag AND ((password | key) NEAR reset$4) AND ("713".clas. | "726". clas. | "380".clas.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 13:41
S71	1840	(reset$4 | default$3 | restor$3) AND (key | password | passcode | "PIN") AND environment$2 AND (variable$1 | value$1) AND (713/1,2,100,182.ccls. | 380/59,277, 286.ccls. | 726/1,2,6,16-18,26,27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409") AND (NOT S70)	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 13:44
S72	0	(reset NEAR key) AND (environment$2 NEAR (variable$1 | value$1)) AND (713/1, 2,100,182.ccls. | 380/59,277,286.ccls. | 726/1,2,6,16-18,26,27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409") AND (NOT S70)	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 13:45
S73	0	(reset NEAR (key | password | passcode)) AND (environment$2 NEAR (variable$1 | value$1)) AND (713/1,2,100,182.ccls. | 380/59,277,286.ccls. | 726/1,2,6,16-18,26, 27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409") AND (NOT S70)	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 13:45
S74	28	((reset | default$3) SAME (key | password | passcode)) AND (environment$2 NEAR (variable$1 | value$1)) AND (713/1,2,100, 182.ccls. | 380/59,277,286.ccls. | 726/1,2, 6,16-18,26,27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409") AND (NOT S70)	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 13:45
S75	99	((reset | default$3) SAME (key | password | passcode)) AND (environment$2 SAME (variable$1 | value$1)) AND (713/1,2,100, 182.ccls. | 380/59,277,286.ccls. | 726/1,2, 6,16-18,26,27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409") AND (NOT S70)	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 13:45
S76	1099	(reset | default$3) AND (key | password | passcode | "PIN") AND environment$2 AND (variable$1 | value$1) AND (713/1,2,100, 182.ccls. | 380/59,277,286.ccls. | 726/1,2, 6,16-18,26,27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409") AND (NOT S70)	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 13:45

S77	1655	(reset | default$3) AND (key | password | passcode | "PIN") AND environment$2 AND (variable$1 | value$1) AND (713/1,2,100, 182.ccls. | 380/59,277,286.ccls. | 726/1,2, 6,16-18,26,27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409") AND (NOT S70)	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 13:45
S78	1840	(reset$4 | default$3 | restor$3) AND (key | password | passcode | "PIN") AND environment$2 AND (variable$1 | value$1) AND (713/1,2,100,182.ccls. | 380/59,277, 286.ccls. | 726/1,2,6,16-18,26,27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409") AND (NOT S70)	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 13:45
S79	28	((reset | default$3) SAME (key | password | passcode)) AND ((environment$2 | "env" | "setenv") NEAR (variable$1 | value$1)) AND (713/1,2,100,182.ccls. | 380/59,277, 286.ccls. | 726/1,2,6,16-18,26,27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409") AND (NOT S70)	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 14:47
S80	30	((reset | default$3) SAME (key | password | passcode)) AND ((environment$2 | "env" | "setenv") NEAR (variable$1 | value$1)) AND (713/1,2,100,182.ccls. | 380/59,277, 286.ccls. | 726/1,2,6,16-18,26,27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 15:04
S81	46	((reset | default$3) SAME (key | password | passcode)) AND ((environment$2 | "env" | "setenv") NEAR (variable$1 | value$1 | flag$1)) AND (713/1,2,100,182.ccls. | 380/59,277,286.ccls. | 726/1,2,6,16-18,26, 27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 16:47
S82	979	((reset$4 | default$3) SAME (key | password | passcode)) AND (variable$1 | value$1 | flag$1) AND (713/1,2,100,182. ccls. | 380/59,277,286.ccls. | 726/1,2,6, 16-18,26,27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 16:51

S83	78	(environment$2 SAME variable) AND ((reset$4 | default$3) SAME (key | password | passcode)) AND (value$1 | flag$1) AND (713/1,2,100,182.ccls. | 380/59,277,286.ccls. | 726/1,2,6,16-18,26, 27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 16:52
S84	76	(environment$2 SAME (variable$1 | value$1)) AND ((reset$4 | default$3) SAME (key | password | passcode)) AND flag$1 AND (713/1,2,100,182.ccls. | 380/59,277, 286.ccls. | 726/1,2,6,16-18,26,27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 16:52
S85	35493	herman.in.	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 16:54
S86	22	herman.in. AND key AND secure AND flag	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 16:54
S87	8	herman.in. AND key AND secure AND flag AND variable	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 16:54
S88	11	(environment$2 SAME (variable$1 | value$1)) AND ((reset$4 | default$3) NEAR (key | password | passcode)) AND flag$1 AND (713/1,2,100,182.ccls. | 380/59,277, 286.ccls. | 726/1,2,6,16-18,26,27.ccls.) AND (@pd<"20040409" | @ad<"20040409" | @prad<"20040409" | @rlad<"20040409")	US-PGPUB; USPAT; USOCR; EPO; DERWENT; IBM_TDB	ADJ	ON	2008/11/24 16:55